

Complete Multiple Tasks in One with Easy-to-read Color Touch Screen.

Pantum M7300 series makes your jobs easier with 3.5 inch color touch screen. It makes your work more efficient with multifunction in one, high print and copy speed and autoduplex printing and scanning meanwhile makes your outputs more affordable and ecofriendly with separate drum unit and toner cartridge. It aims to meet the requirements of small to large workgroups using satisfying function and outstanding performance.



MONO

Easy-to-read 3.5 inch color touch screen



One-step driver installation and direct printing



Office document direct print from mobile devices



Confidential **Printing**



Automatic Duplex Printing and Scanning



USB Disk Direct Printing



WiFi and print from mobile device available for M7300FDW



KEY SPECIFICATIONS

MODEL	■M7300FDN : ■M7300FDW
RINTING	33ppm (A4) / 35ppm (Letter)
Print speed(1)	
Time to First Page®	≤8.5s
Maximum Monthly Duty Cycle	60000 Pages
Recommended Monthly Page Vol	Max 1200x1200 dpi
Print Resolution Printer Languages	·
Processor	PCL5e, PCL6, PS, PDF 600MHz
Memory	512 MB
Duplex Printing	Auto
Control Panel	3.5 inch touch screen
USB Printing	Yes
Security Printing	Yes
Google Cloud Printing	Yes
	,
NFC Connection	No Yes
DPYING 100	00 (44)/05 (4.4)
Copy Speed ⁽¹⁾	33cpm (A4) / 35cpm (Letter)
Time to First Copy ⁽¹⁾	Flatbed: Less than 10s / ADF: Less than 11s
Copy Resolution	Max 600 x 600dpi
Continuous Copy Page	1-99 Page(s)
Zoom	25%~400%
Additional Function	ID copy, Receipt copy, N-up copy, Clone copy, Poster copy, Manual duplex copy, Collated copy
CANNING Scan Type	Flatbed+ADF
Duplex Scanning ⁽¹⁾	Yes, 24ppm (48ipm)
ADF Capacity	
Scan Speed ⁽¹⁾	50 Pages 24 ppm (A4) / 25 ppm (Letter)
Max Scan Size	Flatbed: 216 x 297mm ADF: 216 x 356 mm
Scan Resolution	Flatbed: Max 1200 x 1200dpi
Color Scanning	Yes
Output Function	Scan to PC, Email, FTP, USB
XING	300.710 T 3, E.M.N., 1 7 9 9 2
Fax Type	Mono
Modem Max Speed	33.6Kbps
Fax Resolution	Max 300 x 300 dpi
Fax Memory	650 Pages
Coded System	MH/MR/MMR/JBIG
Compatibility ⁽¹⁾	ITU-T SG3 / ECM
Fax Feature PER HANDLING	PC-FAX(only sending), Junk Fax Barrier, Multi-send, Fax Forwarding, Quick-dial, Group Dial, PC-FAX(only sending), Junk Fax Barrier, Multi-send, Fax Forwarding, Quick-dial, Delayed Send, Auto Redial, Auto Receive, Auto Reduction, Fax To Email Delayed Send, Auto Redial, Auto Receive, Auto Reduction, Mobile Fax, Fax To
Paper Input Tray	250 Pages
Multipurpose Trav	
· · · · · · · · · · · · · · · · · · ·	1 Page
ADF Capacity	50 pages
Paper Output Capacity	150 pages (A4/70g)
Media Type	Plain, Thick, Thin, Transparency, Cardstock, Label, Envelope
Media Size	A4, A5, JIS B5, IS0 B5, A6, Letter, Legal, Executive, Folio, Oficio, Statement, Japanese Postcard, Monarch Env, DL Env, C5 En C6 Env, No.10 Env, ZL, Big 16K, Big 32K, 16K, 32K, B6, Yougata4, Postcard, Younaga3, Nagagata3, Yougata2
Media Weight	Standard Tray: 60-105g/m³ Multipurpose Tray: 60-200g/m³
ENERAL	
Product Dimension (wxdxh)	415 x 360 x 352mm
Weight (without toner cartridge)	10.54kg
Environment	Best Temperature: 10~32°C Relative Humidity: 20%~80%
Noise	Print: 52dB(A) Copy: 54dB(A) Scan: 52dB(A) Standby: 30dB(A)
Power Consumption	Print: Average 550W Standby: Less than 50W Dormant: Less than 2 W
Operating System	Microsoft Windows Server2003/Server2008/Server2012/XP/Vista/Win7/Win8/Win8.1/Win10(32/64 Bit); Mac OS 10.7-10.13; Linux: Ubuntu 12.04/14.04(32/64 Bit)
Mobile Operating system compat	bility iOS 7.0 and above; Android 4.4 and above
Intentos	High Speed USB 2.0
Interface	Net: IEEE 802.3 10/100Base-Tx Net: IEEE 802.3 10/100Base-Tx WiFi: IEEE 802.11b/g/n
Interface	
JPPLIES	-
JPPLIES Cartridge Type	Separate Drum and Toner
JPPLIES	-

⁽¹⁾ Up to (2) As per ISO/IEC 19752 specification (Individual users will experience different results based on their environment and page coverage)

Copyright © 20 Pantum International Limited. The information contained herein is subject to change without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein. *Printer data based on Pantum internal testing