

PANTUM

The New Era for Printing

Reliability is all that matters.

Sick of filling up the paper tray or changing toners? New Pantum high speed automatic duplex P3500 series offers massive paper input up to 1410 pages. This robust machine delivers efficient and reliable printing experience you require for your business.

P3500 Series
Monochrome Laser Printer



Print **12** basketball courts monthly
1.5 basketball courts all at once



Fast Print Speed



**550 Sheet
Optional Paper Tray x 2**



**80000 Page
Monthly Duty Cycle**



**Wi-Fi Connectivity
and Mobile Printing**



**One-Step driver
installation and
direct printing**



WiFi and print from mobile device available for P3500DW

PANTUM

WWW.PANTUM.COM

KEY SPECIFICATIONS



P3500 Series Monochrome Laser Printer

MODEL

■ P3500DN

■ P3500DW

PRINTING

Technology	Mono laser		
Print speed	33ppm (A4) / 35ppm (Letter)		
First print out time	Less than 8.5 seconds		
Maximum Monthly Duty Cycle	80000 pages		
Recommended monthly volume	5000 pages		
Processor speed	600 MHZ		
Memory	256MB (Max : 512MB)		
Resolution(dpi)	1200x1200dpi (Max)		
Printer language	PCL5e, PCL6/XL,PS3, PDF		
Duplex mode	Auto		
Network	Yes		
Wi-Fi	No	Yes	Yes

PAPER HANDLING

Paper Input tray	250 pages
Paper Input tray	60 pages
Optional tray	Yes (550 pages)
Paper Output tray	150 pages
Media sizes	A4, A5, A5L A6, JIS B5, ISO B5, B6, Letter, Legal, Executive, Folio, Oficio, Statement, 16K, Big 16K, 32K, Big 32K, No.10 Env., Monarch Env, DL Env, C5 Env, C6 Env, ZL, Japanese Postcard, custom, Yougata4, Younaga3, Nagagata3, Yougata2
Media types	Multipurpose tray: Plain, Thick(Tough), Thin, Transparency, Cardstock, Label, Envelope Standard tray: Plain, Thin Optional tray: Plain, Thin
Media Weight	Multipurpose tray: 60~200 g/m ² ; Standard tray: 60~105 g/m ² ; Optional tray: 60-105g/m ²

GENERAL

Dimensions (w x d x h)	370x370x286mm (14.6"x14.6"x11.3")		
Display	2 line LCD		
Weight (without toner cartridge)	9.4kg (20.7lb)		
Operating temperature range	Recommended temperature:10-35°C (10-95°F)		
Operating humidity range	Humidity range: 20% - 80%		
Input voltage	110V Model: AC100~127V(±10%), 50Hz/60Hz(±2Hz); 8A 220V Model: AC220~240V((±10%), 50Hz/60Hz(±2Hz); 4A		
Power consumption	Printing: 495W Ready: 50W Sleep: 2W		
Operating system compatibility	Windows Server2003 / 2008 / 2012 / XP / Vista / Win 7 / Win 8 / Win8.1 / Win10 (32/64 Bit); Mac OS 10.7~10.13; Linux: Ubuntu12.04/14.04 (32/64 Bit)		
Interface	HI-SPEED USB 2.0; Net: IEEE 802.3 10/100/1000Base-TX;	; ; ;	HI-SPEED USB 2.0; Net: IEEE 802.3 10/100/1000Base-TX; WiFi: IEEE 802.11b/g/n;

CONSUMABLE

Toner cartridge⁽¹⁾

Starter cartridge: 3000 pages
Replacement capacity: P*-310 (3000 pages); P*-310H (6000 pages); P*-310X (10000 pages)

WHAT'S IN THE BOX

Printer×1/3,000 Pages Toner Cartridge×1/USB Interface Cable×1/
Power Cord×1/CD-ROM×1/Quick Setup Guide×1

(1) As per ISO/IEC 19752 specification (Individual users will experience different results based on their environment and page coverage)

Copyright © 2019 Pantum International Limited. The information contained herein is subject to change without notice. Pantum shall not be liable for technical or editorial errors or omissions contained herein.

*Printer data based on Pantum internal testing.